



S9

SCHWING TECH

**XCMG FOR YOUR SUCCESS**



## 混凝土布料机 Concrete Placing Boom

XUZHOU CONSTRUCTION MACHINERY GROUP CO.,LTD.

XUZHOU XCMG SCHWING MACHINERY CO.,LTD

XCMG IMPORT & EXPORT CO.,LTD

**Tel:** (+86-516) 83111590 87892033 87892301

**Fax:** (+86-516) 87892035

**Email:** [concretemachinery@xcmg.com](mailto:concretemachinery@xcmg.com)

# HGP32

# Concrete Placing Boom

项目 Item	单位 Unit	参数与尺寸 Parameter and dimension	
型号 Model		HGP32	
最大布料半径 Max. placing radius	m	32	
臂架回转角度 Slewing angle of the placing boom	°	370	
工作环境温度 Temperature of work environment	°C	-20~+50	
独立高度 Independent height	m	21	
立柱形式 Mast type		4m+6m	
安装形式 Mounting type		楼面 Floor	
爬升速度 Climbing speed	m/min	0.5~0.8	
爬升形式 Climbing type		油缸顶升式 Top-climbed oil tank	
电机型号 Motor model		YX3-180L-4 V1	
额定功率 Rated Power	Kw	22	
额定电压 / 功率 Rated Voltage/ Frequency		380V/50Hz	
额定转速 Rated Speed	rpm	1470	
系统压力 System pressure	MPa	33	
流量 Flow	L/min	34	
油箱容积 Oil tank capacity	L	120	
控制方式 Control model		近控 / 有线 / 遥控 Panel control/wired control/remote control	
输送管清洗方式 Cleaning methods of delivery pipe		水洗 / 干洗 Washing/dry cleaning	
总质量 Gross mass	t	19.9	
臂架形式 Boom type		4R	
输送管径 Delivery pipeline diameter	mm	DIN 125	
末端软管长度 Length of end hose	m	3	
第一节臂 1 <sup>st</sup> section	长度 Length	mm	9155
	转角 Rotation angle	°	90
第二节臂 2 <sup>nd</sup> section	长度 Length	mm	7815
	转角 Rotation angle	°	180
第三节臂 3 <sup>rd</sup> section	长度 Length	mm	7755
	转角 Rotation angle	°	180
第四节臂 4 <sup>th</sup> section	长度 Length	mm	6682
	转角 Rotation angle	°	240

© Reminder: technical data is subject to upgrade and modification of products without notification.

**UZHOU CONSTRUCTION MACHINERY GROUP CO.,LTD.**  
**UZHOU XCMG SCHWING MACHINERY CO.,LTD.**  
**XCMG IMPORT & EXPORT CO.,LTD.**

Concrete Machinery Export Department  
 Tel: +86-516-87892033 87892301 83111590  
 Fax: +86-516-87892035  
 Email: concretemachinery@xcmg.com